




NOTES:

1. MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-019)
2. COLOR: BLACK.
3. TO FIT IN A $\varnothing 7.9 \pm 0.002$ [$\varnothing 0.313 \pm 0.05$] THREADED HOLE.
 MINIMUM RECOMMENDED PANEL THICKNESS: 6 mm [.236]
 PART CAN ALSO FIT NON THREADED HOLE DIA. 7 mm [.276]
4. PART DESIGNED IN mm, ALTERNATE UNITS FOR REFERENCE ONLY.
5. TOOL REQUIRED FOR INSTALLATION, AND PHILIPS SCREWDRIVER FOR REMOVAL.

			TITLE: BARBED PUSH FASTENER, REMOVABLE				 		DWG IN mm [IN]	
CREATED USING SOLIDWORKS			FILE #: BPFR-1	DWN: SK	APP: S.K.	FINAL				
GENERAL TOLERANCE UNLESS OTHERWISE NOTED			SHEET: 1 OF 1	SHEET SIZE: A	DT: 07/01/08	CHKD: D.Z.	PART #		PRINT TYPE	
±0.25 ANG. ±1°			RE: RICHCO, INC, --	RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		BPFR-1		CA		
A	RELEASED FOR PRODUCTION	SK	12/19/08							
REV.	DESCRIPTION	ENGR.	DATE							